



产品名称: 12V 40kg RS485串行总线舵机
Product Name: 12V 40kg.cm Serial Control RS485 Servo

产品型号 Model No. SM40BL

1. 使用环境条件 Apply Environmental Condition

No.	Item	Specification
1-1	存储温度 Storage Temperature Range	-30℃~80℃
1-2	运行温度 Operating Temperature Range	-20℃~80℃

2. 测试环境 Standard Test Environment

No.	Item	Specification
2-1	温度 Temperature range	25℃ ±5℃
2-2	湿度 Humidity range	65%±10%

3. 机械特性 Mechanical Specification

No.	Item	Specification
3-1	尺寸 Size	A: 46.5mm B: 28.5mm C: 34mm
3-2	重量 Weight	100g
3-3	齿轮类型 Gear type	Steel Gear (Gear Ratio 353:1)
3-6	机构极限角度 Limit angle	No Limiter
3-7	轴承 Bearing	2 Ball bearings
3-8	出力轴 Horn gear spline	25T (OD5.96mm)
3-9	摆臂 Horn type	Aluminium
3-10	外壳 Case	Aluminium
3-11	舵机线 Connector wire	150mm ±5 mm
3-12	马达 Motor	Brushless motor
3-13	防水性能 Splash water resistance	NO

4. 电气特性 Electrical Specification (Function of the Performance)

No.	工作电压 Operating Voltage Range	12V	
4-1*	静态电流 Idle current (at stopped)	40mA	
4-2*	空载速度 No load speed	0.153sec/60degree	65RPM
4-3*	空载电流 Runnig current (at no load)	200mA	
4-4	堵转扭矩 Peak stall torque	40kg.cm	
		556.5oz.in	
4-5	堵转电流 Stall current	2500 mA	
4-6	额定负载 Rated Load	12kg.cm≤	
4-7	额定电流 Rated current	800mA≤	
4-8	KM常数	14.5kg.cm/A	
4-9	电机内阻 Terminal resistance	2.2Ω	

Note: "*"definition is average value when the servo runing with no load



产品名称: 12V 40kg RS485串行总线舵机
 Product Name: 12V 405kg.cm Serial Control RS485 Servo

产品型号 Model No. SM40BL

5. 控制特性 Control Specification:

No.	Item	Specification
5-1	控制信号 Command signal	Bus Packet Communication RS485
5-2	协议类型 Protocol Type	Half duplex Asynchronous Serial Communication
5-3	ID范围 ID range	0-253
5-4	通读速率 Communication Speed	38400bps ~ 1 Mbps
5-5	旋转角度 Running degree	360° (when 0~4096)-CW
5-6	反馈 Feedback	Load, Position, Speed, Input Voltage, Current, Temperature
5-7	位置传感器分辨率 Position Sensor (Resolution)	

6. 外形图 The Drawings

